



256-300

Adjustable Upper Guide
with Roller Covers,
For up to 3" frames, Galvanized



USE: Guide plate for sliding gates.
TYPE: Adjustable gate guide plate with long leaf for fixing.
FIXING: For fixing or welding.
MATERIAL: Body in electrogalvanized steel and rollers in nylon.
RECYCLING: Dispose of the body as ferrous material and the rollers as plastic material in accordance with the current laws in the country of installation.
PARTS SUBJECT TO WEAR: Rollers.
IMPORTANT: The manufacturer reserves the right to modify the characteristics of the product as required without notice. The manufacturer declines any liability for even partial modifications to the product, and the declared performance values are valid only if the installation procedures are carried out by qualified personnel. The roller does not have a load-bearing function, in only having to guide the sash vertically during its sliding movement. It must only be able to withstand minor impacts or sudden unbalancing (wind gusts, light impacts).

| TECHNICAL CHARACTERISTICS | | | | |
|--|----------|-----------|-----------------------|------------------------|
| | | 256-220 | 256-300 | |
| WEIGHT OF PART | | 2,90 Kg | 4,55 Kg | |
| GATE MIN. THICKNESS | | 20 mm | 20 mm | |
| GATE MAX. THICKNESS | | 80 mm | 120 mm | |
| MAINTENANCE FREQUENCY | | | | |
| PRIVATE HOME | COMPANY | WAREHOUSE | CONDOMINIUM <20 UNITS | CONDOMINIUM > 20 UNITS |
| 2 YEARS* | 2 YEARS* | 2 YEARS* | 1 YEAR* | 1 YEAR* |
| Check rollers. | | | | |
| Check fixing or welds. | | | | |
| *The scheme refers to a normal workplace (not marine or particularly aggressive environments). | | | | |

Illustrations not to scale and are for reference only. Imperial units shown are for reference only, use millimeters for most accurate sizes.

All pictures, technical drawings and related specifications belong to Fratelli Comunello Spa and they are defended by rules of copyright. All uses not expressly authorized will be legally prosecuted. Product specifications are subject to change without notice.

255-220-C, 256-220 or 256-300

